PREMIUM AUTOMATIC TRANSMISSION FLUID DATA SHEET



TYPE M5

252-2005



Beck/Arnley Premium Automatic Transmission Fluid for Type M5 is a superior quality formulation of high-performance base oils and carefully selected additives. It includes a unique mix of friction materials for the specific pressure settings present in Mazda automatic transmissions, which helps promote optimum shift quality.

This product is chemically balanced to provide protection for seals and o-rings against corrosion, and metal components from rust and wear as well as resistance to oxidation to prolong the life of the fluid. A special high viscosity index fluid helps to promote smooth shifting in extreme temperatures.

Use this Premium Automatic Transmission Fluid for Type M5 when Type M3 and M5 automatic transmission fluid is required for Mazda vehicles.

Always check owner's manual for proper application.

FORMULATED FOR	OE REFERENCE NUMBER
MAZDA	0000-77-110E-01 (M3)
	0000-77-112E-01 (M5)

ATTRIBUTES	
APPEARANCE	Red
FLASH POINT	208°C/406°F
POUR POINT	-50°C/-58°F
VISCOSITY AT 40°C	35.0 cSt
VISCOSITY AT 100°C	7.4 cSt
VISCOSITY INDEX	182
DYNAMIC VISCOSITY AT -40°C	30.64
DENSITY AT 15°C	0.85

UNIT SIZE	PART NUMBER
1 QT - 32 FL Q7 (946 ML)	252-2005



Braking | Engine: Electrical | Engine: Mechanical | Fluids | Steering/Suspension/Driveline