HYDRAULIC FLUID DATA SHEET





FS11 HF

FORMULATED FOR

BMW/MINI

LAND ROVER

MERCEDES-BENZ

JAGUAR

PORSCHE

UNIT SIZE

1.06 QT. (1 LITER)

Reference CHF 202 or CHF 11S

(i.e. brake fluids DOT 3/4/5.1 or DOT5)

SAAB VOLVO

AUDI/VOLKSWAGEN



OE REFERENCE NUMBER

G 004 000 M2

JLM21112

LR003401

30741424

83 29 0 429 576

001 989 24 03 10

000 043 206 56 000 043 305 74 93 16 0548

PART NUMBER

252-0028

Beck/Arnley Premium Fully Synthetic Hydraulic Fluid is a superior quality formulation of state-of-the-art additives and carefully selected, high performance synthetic base oils for specific European nameplates. Specifically developed for use in hydraulically supported lever control, power steering and shock absorbers.

Specific to vehicles requiring CHF 11S Hydraulic Fluid.

This fully synthetic hydraulic fluid has outstanding viscosity/temperature behavior providing reliable operation at both high and low temperatures. It has excellent aging and oxidation stability, due to the carefully selected synthetic base oils with excellent sealing compatibility.

Always check owner's manual for proper application.

DIN	51 524 T3
ISO	7308
AUDI/ VOLKSWAGEN	TL 52 146
CHRYSLER/DODGE/JEEP	MS-11655
FORD	WSS-M2C204-A
MAN	M 3289
MERCEDES-BENZ	MB 345.0
ZF	TE-ML 02K
ATTRIBUTES	
APPEARANCE	Green
FLASH POINT	130°C/266°F
POUR POINT	-51°C/-60°F
	01 0/
VISCOSITY AT 40°C	21 mm²/s
	21 mm ² /s 6.2 mm ² /s
VISCOSITY AT 40°C VISCOSITY AT 100°C VISCOSITY INDEX	



Braking

Engine: Electrical

252-0028 (FS11 HF) Premium Synthetic Hydraulic Fluid must not be mixed with any glycol or silicone based fluids

e: Mechanical |

Steering/Suspension/Driveline