

SAFETY DATA SHEET

Product Name: PPE

Beck/Arnley Automatic Transmission Fluid Type DW-1 252-2007, 12 x 1 Qt.



Revision Date: 17-Aug-2018 Revision Number: 1

 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product Name: Beck/Arnley Automatic Transmission Fluid Type DW-1, 12 x 1 Qt.

Other means of identification

Product Code: 252-2007

1.2 Recommended use of the chemical and restrictions on use

Recommended Use: Automotive Lubricant

1.3 Details of the supplier of the safety data sheet

Manufactured by: Beck/Arnley

2375 Midway Lane Smyrna, TN 37167

Telephone 615-220-3200

Email: beckcustomerservice@fmmotorparts.com

24 Hour Emergency Phone Number: INFOTRAC

1-800-535-5053

Revision Date: 17-Aug-2018

2. HAZARDS IDENTIFICATION

2.1 Classification

This material is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) and WHMIS 2015

Acute toxicity - Oral	Not classified
Acute toxicity - Dermal	Not classified
Acute Toxicity - Inhalation (Gases)	Not classified
Acute Toxicity - Inhalation (Vapors)	Not classified
Acute Toxicity - Inhalation (Dusts/Mists)	Not classified
Skin corrosion/irritation	Not classified
Serious eye damage/eye irritation	Not classified
Respiratory sensitization	Not classified
Skin sensitization	Not classified
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
Specific target organ toxicity (single exposure)	Not classified
Specific target organ toxicity (repeated exposure)	Not classified
Aspiration toxicity	Not classified
Physical hazards	Not classified

2.2 Label elements

Not a dangerous substance or mixture according to the Globally Harmonized System (GHS)

Hazards not otherwise classified (HNOC) Not applicable

2.3 Other information

Other hazards May be harmful in contact with skin

Harmful to aquatic life

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Not applicable

3.2 Mixture

Non-Hazardous Components

Chemical name	CAS No.	Weight-%
Lubricating Base Stocks	Mixture	80-90

^{*} The petroleum base oils contained in this product have been highly refined by a variety of processes including solvent extraction, hydrotreating, and dewaxing to remove aromatics and improve performance characteristics. All of the oils meet the IP-346 criteria of less than 3 percent PAH's and therefore none are listed as a carcinogen by NTP, IARC, or OSHA

. , po 5.0 1 20 2001, 12 X 1 Q

4. FIRST AID MEASURES

4.1 First Aid Measures

General Advice If symptoms persist, call a physician. Take a copy of the Safety Data Sheet when going for

medical treatment.

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If eye irritation

Revision Date: 17-Aug-2018

persists: Get medical advice/attention.

Skin Contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. If skin irritation persists, call a physician.

Inhalation Move to fresh air in case of accidental inhalation of vapors. If breathing is difficult, give

oxygen. If not breathing, give artificial respiration. Call a physician immediately.

Ingestion Do not induce vomiting without medical advice. If vomiting occurs naturally, have casualty

lean forward to reduce the risk of aspiration. If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms No Information available.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

FIRE-FIGHTING MEASURES

Flammable Properties NFPA: Class IIIB Combustible Liquid

5.1 Suitable Extinguishing Media: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment

Unsuitable Extinguishing Media: Do not use a solid water stream as it may scatter and spread fire.

<u>5.2 Specific Hazards Arising from the Chemical</u>

Keep product and empty container away from heat and sources

of ignition.

Hazardous combustion products During a fire, smoke may contain the original material in addition

to combustion products of varying composition which may be toxic and / or irritating. Combustion products may include and

are not limited to: Carbon oxides

Phosphorus compounds (POx) Calcium Oxides (CaOx) Nitrogen oxides (NOx)

Sulphur oxides

5.3 Protective Equipment and Precautions for Firefighters As in any fire, wear self-contained breathing apparatus

pressure-demand, MSHA/NIOSH (approved or equivalent) and

full protective gear.

ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

•

Personal precautions Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists. Use personal

protection recommended in Section 8. Ensure adequate ventilation. Remove all sources of

Revision Date: 17-Aug-2018

ignition.

6.2. Environmental precautions

Environmental Precautions See section 12 for additional ecological information. Prevent further leakage or spillage if

safe to do so. Prevent product from entering drains. Do not allow into any sewer, on the ground or into any body of water. Do not flush into surface water or sanitary sewer system. Large Spills: Dike far ahead of liquid spill for later recovery and disposal. Prevent entry into

waterways, sewers, basements or confined areas.

6.3 Methods and material for containment and cleaning up

Methods for Clean-up Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth,

diatomaceus earth, vermiculite) and place in container for disposal according to local /

national regulations (see section 13).

Spill Management

LARGE SPILLS Eliminate sources of ignition. Prevent additional discharge of material if possible to do so

without hazard. For small spills implement cleanup procedures; for large spills implement cleanup procedures and, if in public area, keep public away and advise authorities. Also, if this product is subject to CERCLA reporting (see Section 15 Regulatory Information) notify

the National Response Center.

WATER SPILLS Prevent liquid entering sewers, watercourses, or low areas. Contain spilled liquid with sand

or earth. Recover by pumping or with suitable absorbent. If liquid is too viscous for pumping, scrape up. Consult an expert on disposal of recovered material and ensure

conformity to local disposal regulations.

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Handling Do not breathe vapors, spray, or mist. Avoid contact with eyes,

skin and clothing. Wear personal protective equipment. Remove and wash contaminated clothing before re-use. Keep away from open flames, hot surfaces and sources of ignition. Should not be

released into the environment.

Safe Handling Advice Handle in accordance with good industrial hygiene and safety

practices. Take precautionary measures against static

discharges.

7.2. Conditions for safe storage, including any incompatibilities

Storage Keep in properly labeled containers. Keep container tightly closed

in a dry and well-ventilated place.

Technical measures/Precautions Ensure adequate ventilation.

Incompatible Materials and/or Coatings No Information available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

2.

8.1 Control Parameters

Chemical name	OSHA PEL	ACGIH TLV	ACGIH OEL (STEL)	NIOSHT REL TWA	ILA IHG	ILA ROEG	ILA Internal Exposure Limit
Oil mist, mineral	TWA: 5 mg/m ³	TWA: 5 mg/m³		TWA 5 mg/m ³ ST 10 mg/m ³			

8.2 Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Revision Date: 17-Aug-2018

Personal Protective Equipment

Eye/face protection Safety glasses equipped with side shields are recommended as minimum protection in

industrial settings.

Skin protection Choose the appropriate protective clothing and gloves based on the tasks being performed

to avoid exposed skin surfaces. Glove Type: Neoprene, Nitriles

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

General Hygiene Considerations

Clean equipment, work area and clothing regularly. Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practices.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance Clear Red
Physical state Liquid
Odor Not available

Odor Threshold No Information available

pH Not applicableMelting point / melting range Not applicable

Boiling point / boiling range No Information available

Flash Point 170 °C / 338 °F COC ASTM D92

Evaporation Rate

Flammability Limit in Air

Explosion Limits

Vapor pressure @20 °C (kPa)

No Information available
No Information available
No Information available

Vapor pressure @20 5 (kt a)No Information availableVapor densityNo Information availableDensity0.85 g/cm³ @15°CSolubility(ies)No Information availablePartition coefficientNo Information availableAutoignition TemperatureNo Information availableDecomposing TemperatureNo Information available

Kinematic viscosity @ 40C = 24.5 cSt; @ 100C = 7.0 cSt

Revision Date: 17-Aug-2018

Other Information

10. STABILITY AND REACTIVITY

10.1 Reactivity

Reactivity The product is chemically stable.

10.2 Chemical stability

Chemical Stability Stable under recommended storage conditions.

10.3 Possibility of Hazardous Reactions

Possibility of Hazardous Reactions None under normal processing.

10.4 Conditions to avoid

Conditions to Avoid Heat, flames and sparks.

10.5 Incompatible materials

Incompatible Materials Strong oxidizing agents

10.6 Hazardous Decomposition Products

Hazardous decomposition products

Thermal decomposition can lead to release of irritating gases and

vapors.

11. TOXICOLOGICAL INFORMATION

11.1 Information on likely routes of exposure

Inhalation May cause irritation of respiratory tract.

Eye contact May cause slight irritation.

Skin Contact May cause skin irritation and/or dermatitis.

Ingestion May be harmful if swallowed.

11.2 Information on toxicological effects

Symptoms No Information available

11.3 Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Not classified.

Serious eye damage/eye

Mutagenic effects

irritation

Not classified.

Not classified.

Sensitization Not classified.

Beck/Arnley Automatic Transmission Fluid Type DW-1 252-2007, 12 x 1 Qt.

11.4 Carcinogenicity

Carcinogenicity No component of this product present at levels greater than or equal to 0.1% is identified as

a known or anticipated carcinogen by NTP, IARC, OSHA or ACGIH.

Legend: NTP (National Toxicology Program), IARC (International Agency for Research on Cancer),

OSHA (Occupational Safety and Health Administration of the US Department of Labor),

Revision Date: 17-Aug-2018

ACGIH (American Conference of Governmental Industrial Hygienists)

Reproductive Effects Not classified.

STOT - single exposure Not classified

STOT - repeated exposure Not classified

Aspiration hazard Not classified.

11.5 Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document _.

Product Information (Estimated):

ATEmix (oral) >5,000 mg/kg
ATEmix (dermal) >2,000 mg/kg
ATEmix (inhalation-dust/mist) >5 mg/l

12. ECOLOGICAL INFORMATION

12.1 Ecotoxicity

Ecotoxicity effects Harmful to aquatic life. Plants and animals may experience harmful or fatal effects when

coated with petroleum products. Petroleum-based (mineral) lubricating oils normally will float on water. In stagnant or slow-flowing waterways, an oil layer can cover a large surface area. As a result, this oil layer might limit or eliminate natural atmospheric oxygen transport into the water. With time, if not removed, oxygen depletion in the waterway may be

sufficient to cause a fish kill or create an anaerobic environment.

Unknown aquatic toxicity 8.13 % of the mixture consists of component(s) of unknown hazards to the aquatic

environment

<u>12.2 Persistence and degradability</u>

The hydrocarbons in this material are not readily biodegradable,

but since they can be degraded by microorganisms, they are

regarded as inherently biodegradable.

12.3 Bioaccumulation/Accumulation No Information available

12.4 Mobility in Environmental Media No Information available.

12.5 Other adverse effects:

No Information available

PBT and vPvB assessment No Information available

13. DISPOSAL CONSIDERATIONS

Hazard characteristic and regulatory waste stream classification can change with product use. Accordingly, it is the responsibility of the user to determine the proper storage, transportation, treatment and/or disposal methodologies for spent materials and residues at the time of disposition.

Waste Disposal Method This material, as supplied, is not a hazardous waste according to Federal regulations (40

CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local

Revision Date: 17-Aug-2018

regulations for additional requirements.

Contaminated packaging Dispose of in accordance with local regulations.

Not regulated

14.TRANSPORT INFORMATION

DOT - Non bulk Not regulated

IATA Not regulated

IMDG Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA	All ingredients are on the inventory or exempt from listing
DSL	All ingredients are on the inventory or exempt from listing
ENCS	All ingredients are on the inventory or exempt from listing
KECL	All ingredients are on the inventory or exempt from listing
AICS	All ingredients are on the inventory or exempt from listing
REACH	All ingredients are on the inventory or exempt from listing

USA		
WOA		

Federal Regulations

SARA 313

DOT - Bulk

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazardous Categorization

Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

CERCLA/SARA 302 & 304

Section 302 & 304 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 355.

	Chemical name	CAS No.	Weight-%	RQ	TPQ
Ī	Methyl methacrylate	80-62-6	<0.1	RQ 1000lb final RQ	
				RQ 454kg final RQ	
Ī	Phenol	108-95-2	<0.01	RQ 1000lb final RQ	500 lb lower TPQ

Revision Date: 17-Aug-2018

	RQ 454kg final RQ	10000 lb upper TPQ

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61) This product contains the following HAPs:

Chemical name	CAS No.	Weight-%	HAPS data
Methyl methacrylate	80-62-6	<0.1	X
Phenol	108-95-2	<0.01	X

<u>CWA (Clean Water Act)</u>
This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CAS No.	Weight-%	U.S CWA (Clean Water Act)
Methyl methacrylate	80-62-6	<0.1	X
Phenol	108-95-2	<0.01	X

State Regulations

California Proposition 65

Label:

This product does not contain any Proposition 65 chemicals

State Right-to-Know

Chemical name	CAS No.	Weight-%	New Jersey
Petroleum distillates, hydrotreated light paraffinic	64742-55-8	60-70	X
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	1-5	Х
Petroleum distillates, solvent-refined heavy paraffinic	64741-88-4	1-5	Х

Chemical name	CAS No.	Weight-%	Massachusetts
Petroleum distillates, hydrotreated light	64742-55-8	60-70	X
paraffinic			

Chemical name	CAS No.	Weight-%	Pennsylvania
Petroleum distillates, hydrotreated light	64742-55-8	60-70	X
paraffinic			

Canada

This material has been classified in accordance with the WHMIS 2015 regulation

Chemical name	CAS No.	Weight-%	NPRI
Petroleum distillates, hydrotreated light	64742-47-8	<1	Listed
Methyl methacrylate	80-62-6	<0.1	Listed
Phenol	108-95-2	<0.01	Listed
Diphenylamine	122-39-4	<0.01	Listed

Legend

NPRI - National Pollutant Release Inventory

16. OTHER INFORMATION

1 0

Health hazards 1 Flammability 1 Instability 0

Revision Date: 17-Aug-2018

Prepared By: Sam Fritsche

Revision Date: 17-Aug-2018

Revision Summary: Review

Disclaimer:

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet