

SAFETY DATA SHEET

Product Name:

Beck/Arnley Automatic Transmission Fluid Type WS 252-2006, 12 x 1 Qt.









Revision Date: 26-Apr-2018 Revision Number: 2

IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product Name: Beck/Arnley Automatic Transmission Fluid Type WS

12 x 1 Qt.

Other means of identification

Product Code: 252-2006

Synonyms Not available

1.2 Recommended use of the chemical and restrictions on use

Recommended Use Automotive Lubricant

Uses advised against No information available

1.3. Details of the supplier of the safety data sheet

Distributed by Beck/Arnley

2375 Midway Lane Smyrna, TN 37167

Telephone: 615-220-3200

Email: beckcustomerservice@fmmotorparts.com

24 Hour Emergency Phone Number: INFOTRAC

1-800-535-5053

Type WS 252-2006, 12 x T Qt.

Revision Date: 26-Apr-2018

2. HAZARDS IDENTIFICATION

2.1 Classification

This material is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) and WHMIS 2015

Acute toxicity - Oral	Not classified
Acute toxicity - Dermal	Not classified
Acute Toxicity - Inhalation (Gases)	Not classified
Acute Toxicity - Inhalation (Vapors)	Not classified
Acute Toxicity - Inhalation (Dusts/Mists)	Not classified
Skin corrosion/irritation	Not classified
Serious eye damage/eye irritation	Not classified
Respiratory sensitization	Not classified
Skin sensitization	Category 1
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
Specific target organ toxicity (single exposure)	Not classified
Specific target organ toxicity (repeated exposure)	Not classified
Aspiration toxicity	Not classified
Physical hazards	Not classified
Physical Hazards	None

2.2 Label elements



Hazards not otherwise classified (HNOC)

•	
Signal word	Warning
Hazard statements	H317 - May cause an allergic skin reaction
Precautionary Statements - Prevention:	P261 - Avoid breathing dust, fume, gas, mist, vapors or spray P272 - Contaminated work clothing should not be allowed out of the workplace P280 - Wear protective gloves Avoid release to the environment
Precautionary Statements - Response:	P321 - Specific treatment (see supplemental first aid instructions on this label) P362 + P364 - Take off all contaminated clothing and wash it before reuse
Skin	P302 + 352 - IF ON SKIN: Wash with plenty of soap and water P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention P363 - Wash contaminated clothing before reuse
Precautionary Statements - Disposal:	P501 - Dispose of contents/ container to an approved waste disposal plant

Not applicable

Type W5 252-2006, 12 X T QL

2.3 Other information

Other hazards

- · May be harmful in contact with skin
- Toxic to aquatic life
- · Harmful to aquatic life with long lasting effects

Revision Date: 26-Apr-2018

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Not applicable

3.2 Mixtures

Hazardous Components

Chemical name	CAS No.	Weight-%	US GHS Classification	Notes
Alkyl ester carboxylic acid	68015-93-0	<1	Skin Irrit. 2 (H315)	
			Eye Dam. 1 (H318)	
			Skin Sens. 1 (H317)	
				ļ

Non-Hazardous Components

Chemical name	CAS No.	Weight-%
Lubricating Base Stocks	Mixture	85-95

4. FIRST AID MEASURES

4.1 First Aid Measures

General Advice If symptoms persist, call a physician. Take a copy of the Safety Data Sheet when going for

medical treatment.

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If eye irritation

persists: Get medical advice/attention.

Skin Contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. Wash contaminated clothing before re-use. Call a physician

immediately.

Inhalation Move to fresh air in case of accidental inhalation of vapors. If breathing is difficult, give

oxygen. If not breathing, give artificial respiration. Call a physician immediately.

Ingestion: Do not induce vomiting without medical advice. If vomiting occurs naturally, have casualty

lean forward to reduce the risk of aspiration. If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

Type WS 252-2006, 12 x 1 Qt.

5. FIRE-FIGHTING MEASURES

Flammable Properties NFPA: Class IIIB Combustible Liquid

5.1 Suitable Extinguishing Media: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment

Unsuitable Extinguishing Media:Do not use a solid water stream as it may scatter and spread fire.

<u>5.2 Specific Hazards Arising from the Chemical</u>

Keep product and empty container away from heat and sources

of ignition.

Hazardous combustion products: During a fire, smoke may contain the original material in addition

to combustion products of varying composition which may be toxic and / or irritating. Combustion products may include and

Revision Date: 26-Apr-2018

are not limited to: Carbon oxides Calcium oxides Nitrogen oxides (NOx) Phosphorus oxides Oxides of sulfur

5.3 Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and

full protective gear.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists. Use personal

protection recommended in Section 8. Ensure adequate ventilation. Remove all sources of

ignition.

6.2 Environmental Precautions

Environmental Precautions See section 12 for additional ecological information. Prevent further leakage or spillage if

safe to do so. Prevent product from entering drains. Do not allow into any sewer, on the ground or into any body of water. Do not flush into surface water or sanitary sewer system. Large Spills: Dike far ahead of liquid spill for later recovery and disposal. Prevent entry into

waterways, sewers, basements or confined areas.

6.3 Methods and material for containment and cleaning up

Methods for Clean-up Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth,

diatomaceus earth, vermiculite) and place in container for disposal according to local /

national regulations (see section 13).

Spill Management

LARGE SPILLS Eliminate sources of ignition. Prevent additional discharge of material if possible to do so

without hazard. For small spills implement cleanup procedures; for large spills implement cleanup procedures and, if in public area, keep public away and advise authorities. Also, if this product is subject to CERCLA reporting (see Section 15 Regulatory Information) notify

the National Response Center.

WATER SPILLS Prevent liquid entering sewers, watercourses, or low areas. Contain spilled liquid with sand

or earth. Recover by pumping or with suitable absorbent. If liquid is too viscous for pumping, scrape up. Consult an expert on disposal of recovered material and ensure

Type ws 252-2006, 12 x 1 Qt.

conformity to local disposal regulations.

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Handling Do not breathe dusts or mists. Avoid contact with eyes, skin and

clothing. Wear protective gloves, protective clothing, eye protection, and face protection. Use personal protection recommended in Section 8. Wash hands thoroughly after handling. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product.

Revision Date: 26-Apr-2018

Should not be released into the environment.

Safe Handling Advice Wear personal protective equipment. Do not breathe vapors,

spray, or mist. Use product only in closed system.

7.2. Conditions for safe storage, including any incompatibilities

Storage Keep in properly labeled containers. Keep container tightly closed

in a dry and well-ventilated place.

Technical measures/Precautions Ensure adequate ventilation. To avoid ignition of vapors by static

electricity discharge, all metal parts of the equipment must be

grounded.

Incompatible Materials and/or Coatings

No information available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Exposure Guidelines This product does not contain any hazardous materials with occupational exposure limits

established by the region specific regulatory bodies.

Other Exposure Guidelines (If Generated)

 the Exposure Guidennes (ii	oonoratoa,						
Chemical name	OSHA PEL	ACGIH TLV	ACGIH OEL (STEL)	NIOSHT REL TWA	ILA IHG	ILA ROEG	ILA Internal Exposure Limit
Oil mist, mineral	TWA: 5 mg/m ³	TWA: 5 mg/m ³		TWA 5 mg/m ³ ST 10 mg/m ³			

8.2 Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal Protective Equipment

Beck/Arnley Automatic Transmission Fluid Type WS 252-2006, 12 x 1 Qt.

Type ws 252-2006, 12 x 1 Qt.

Eye/face protection Safety glasses equipped with side shields are recommended as minimum protection in

industrial settings. If splashes are likely to occur wear tight fitting safety goggles and/or

Revision Date: 26-Apr-2018

face-shield.

Skin protection Wear protective gloves/clothing. Long sleeved clothing. Choose the appropriate protective

clothing / gloves based on the tasks being performed to avoid exposed skin surfaces.

Glove Type: Neoprene, Nitriles

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

General Hygiene Considerations When using, do not eat, drink or smoke. Clean equipment, work area and clothing regularly.

PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance Red / Clear Physical state Liquid Odor Strong

Odor Threshold No information available

pH Not applicable
Melting point / melting range Not applicable

Boiling point / boiling range No information available

Flash Point > 165 °C / 329 °F No information available

No information available **Evaporation Rate** Flammability Limit in Air No information available **Explosion Limits** No information available Vapor pressure No information available **Vapor Density** No information available No information available Solubility(ies) **Partition coefficient** No data available **Autoignition Temperature** No information available **Decomposing Temperature** No information available

Dynamic viscosity - VALUE 1 @ 40C = 22.80 cSt; @ 100C = 5.26 cSt

Other Information

10. STABILITY AND REACTIVITY

10.1 Reactivity

Reactivity The product is chemically stable

10.2 Chemical Stability

Chemical Stability Stable under normal conditions.

10.3 Possibility of hazardous reactions

Possibility of Hazardous ReactionsNone under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

10.4 Conditions to Avoid

Beck/Arnley Automatic Transmission Fluid Type WS 252-2006, 12 x 1 Qt.

Type WS 252-2006, 12 X 1 Qt.

Revision Date: 26-Apr-2018

Conditions to Avoid Heat, flames and sparks.

10.5 Incompatible Materials

Incompatible Materials Strong oxidizing agents

10.6 Hazardous Decomposition Products

Hazardous decomposition products

Thermal decomposition can lead to release of irritating gases and

vapors.

11. TOXICOLOGICAL INFORMATION

11.1 Information on likely routes of exposure

Inhalation May cause irritation of respiratory tract.

Eye contact May cause slight irritation.

Skin Contact May cause an allergic skin reaction.

Ingestion: May be harmful if swallowed.

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Alkyl ester carboxylic acid 68015-93-0	> 2,000 mg/kg (Rat)	> 3,160 mg/kg (Rabbit)	

11.2 Information on toxicological effects

Symptoms No information available

11.3 Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Not classified.

Serious eye damage/eye

irritation

Not classified.

Sensitization May cause an allergic skin reaction.

Mutagenic effects Not classified.

11.4 Carcinogenicity

Carcinogenicity No component of this product present at levels greater than or equal to 0.1% is identified as

a known or anticipated carcinogen by NTP, IARC, OSHA or ACGIH.

Leaend:

NTP (National Toxicology Program) ACGIH (American Conference of Governmental Industrial Hygienists) IARC (International Agency for Research on Cancer) OSHA (Occupational Safety and Health Administration of the US Department of Labor)

Reproductive Effects Not classified.

STOT - single exposure Not classified

STOT - repeated exposure Not classified

Aspiration hazard Not classified.

11.5 Acute toxicity

Revision Date: 26-Apr-2018

The following values are calculated based on chapter 3.1 of the GHS document.

Product Information (Estimated):

ATEmix (oral) > 5,000 mg/kgATEmix (dermal) > 2,000 mg/kgATEmix (inhalation-dust/mist) > 5 mg/l

12. ECOLOGICAL INFORMATION

12.1 Ecotoxicity

Ecotoxicity effects Toxic to aquatic life. Harmful to aquatic life with long lasting effects. Plants and animals may

experience harmful or fatal effects when coated with petroleum products. Petroleum-based (mineral) lubricating oils normally will float on water. In stagnant or slow-flowing waterways, an oil layer can cover a large surface area. As a result, this oil layer might limit or eliminate natural atmospheric oxygen transport into the water. With time, if not removed, oxygen depletion in the waterway may be sufficient to cause a fish kill or create an anaerobic

environment.

Unknown aquatic toxicity 8.99 % of the mixture consists of component(s) of unknown hazards to the aquatic

environment

12.2 Persistence and degradability No information available.

12.3 Bioaccumulation/Accumulation No information available

12.4. Mobility in soil No information available

PBT and vPvB assessment No information available

No information available 12.5 Other adverse effects:

13. DISPOSAL CONSIDERATIONS

Hazard characteristic and regulatory waste stream classification can change with product use. Accordingly, it is the responsibility of the user to determine the proper storage, transportation, treatment and/or disposal methodologies for spent materials and residues at the time of disposition.

This material, as supplied, is not a hazardous waste according to Federal regulations (40 **Waste Disposal Method**

CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local

regulations for additional requirements.

Contaminated packaging Dispose of in accordance with local regulations.

14.TRANSPORT INFORMATION

Not regulated **DOT - Non bulk** Not regulated DOT - Bulk

Type WS 252-2006, 12 X 1 Qt.

Revision Date: 26-Apr-2018

IATA Not regulated

IMDG/IMO Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA	All ingredients are on the inventory or exempt from listing					
DSL	All ingredients are on the inventory or exempt from listing					
NDSL	There are ingredien	ts listed on the NDSL Invento	ory List			
Chemical name	NDSL	CAS No.	Weight-%			
Alkenyl dicarboxylamide	X	ACC 147376	1-5			
Alkyl Phosphites	X AAC 151872 <1					
ELINCS	Contains an ELINCS substance					
ENCS	All ingredients are on the inventory or exempt from listing					
IECSC	All ingredients are on the inventory or exempt from listing					
KECL	All ingredients are on the inventory or exempt from listing					
PICCS	All ingredients are or	n the inventory or exempt fror	n listing			
AICS	Does not comply					
NZIoC	Does not comply					
REACH	All ingredients are or	n the inventory or exempt from	n listing			

USA

Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazardous Categorization

Acute health hazardSkin SensitizerChronic Health HazardSkin Sensitizer

Fire hazard No
Sudden Release of Pressure Hazard No
Reactive Hazard No

CERCLA/SARA 302 & 304

Section 302 & 304 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 355.

Chemical name	CAS No.	Weight-%	RQ	TPQ
Methyl methacrylate	ethacrylate 80-62-6 <0.1 F		RQ 1000lb final RQ	
			RQ 454kg final RQ	
Benzene 71-43-2		<0.001	RQ 10lb final RQ	
			RQ 4.54kg final RQ	

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

Chemical name	CAS No.	Weight-%	HAPS data

Type vv3 252-2006, 12 x T Qt.

Revision Date: 26-Apr-2018

Methyl methacrylate	80-62-6	<0.1	Χ
Benzene	71-43-2	<0.001	X

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CAS No.	CAS No. Weight-%	
			Act)
Methyl methacrylate	80-62-6	<0.1	X
Benzene	71-43-2	<0.001	X

State Regulations

California Proposition 65

Label:



warning. Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Chemical name	CAS No.	Weight-%	California Prop. 65	Maximum Allowable Dose for Reproductive Toxicity (MADLS)	Safe Harbor Limits for Cancer-causing Chemicals (NSRLs)
Benzene	71-43-2	<0.001	Carcinogen Developmental Male Reproductive	24µg/dayoral 49µg/dayinhalation	6.4 μg/day oral 13 μg/day inhalation

State Right-to-Know

Chemical name	CAS No.	Weight-%	New Jersey
distillates (petroleum), hydrotreated light	64742-55-8	20-30	Х
paraffinic			
Petroleum distillates, hydrotreated heavy	64742-54-7	10-20	X
paraffinic			
Alkenyl dicarboxylamide	ACC 147376	1-5	X
Petroleum distillates, solvent dewaxed heavy	64742-65-0	1-5	X
paraffinic			

Chemical name	CAS No.	Weight-%	Massachusetts
distillates (petroleum), hydrotreated light	64742-55-8	20-30	X
paraffinic			

Chemical name	CAS No.	Weight-%	Pennsylvania
distillates (petroleum), hydrotreated light	64742-55-8	20-30	X
paraffinic			
Alkenyl dicarboxylamide	ACC 147376	1-5	X
Petroleum distillates, solvent dewaxed heavy	64742-65-0	1-5	X
paraffinic			
Amines, polyethylenepoly-, reaction products		1-5	X
with succinic anhydride polybutenyl derivitives			

New Jersey Worker and Community Right-to-Know Act:

Type WS 252-2006, 12 X 1 Qt.

Under the New Jersey Right-to-Know Act L. 1983 Chapter 315 N.J.S.A. 34:5A-1 et. seq., the product is to be identified as follows: PETROLEUM OIL (Automatic Transmission Fluid)

Canada


This material has been classified in accordance with the WHMIS 2015 regulation

Chemical name	CAS No.	Weight-%	NPRI
Petroleum distillates, hydrotreated light	64742-47-8	<0.1	Listed
Methyl methacrylate	80-62-6	<0.1	Listed
Diphenylamine	122-39-4	<0.01	Listed
Benzene	71-43-2	<0.001	Listed

Legend

NPRI - National Pollutant Release Inventory

16. OTHER INFORMATION



Health hazards 2 Flammability 1 Instability 0

Revision Date: 26-Apr-2018

Prepared By Sam Fritsche

Revision Date: 26-Apr-2018

Revision Summary: Prop 65 change

Disclaimer:

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet